



PW1S

Single Wide Proof Box

STANDARD FEATURES

- Patented air flow system
- Easy access heat and humidity system
 - Internally mounted
 - No flushing required
- Field reversible door
- Eye-level digital control panel
 - Set heat/humidity system
 - Four independent timers
- Stainless steel interior and exterior
- Modular panel construction with cam lock attachment
- Field assembled – shipped knocked down
- Open floor – no ramp required
- 99.5" overall height to match rack oven

OPTIONS & ACCESSORIES

- Low profile, 94" overall height
- Stainless steel floor – no ramp required
- Interior light
- Prison package
- Upper side trim – 1 or 2 sides

MODEL CONFIGURATIONS

- 40.5"D** – May be shipped assembled
 - One Single End, Two Single Side or One Double Side Load Racks
- 60.5"D**
 - Two Single End, Three Single Side or One Double Side Load Racks
- 80.5"D**
 - Three Single End, Four Single Side or Two Double Side Load Racks
- 100.5"D**
 - Four Single End, Five Single Side or Two Double Side Load Racks
- 120.5"D**
 - Five Single End, Six Single Side or Three Double Side Load Racks



Area Reserved For Consultant & Contractor Approvals



19220 State Route 162 East
Orting, WA 98360
www.baxtermfg.com


Factory
(360) 893-5554

Customer Care
(800) 777-2828
or
(800) 333-7447

Customer Care Fax
(937) 332-2852



PW1S Single Wide Proof Box



*94.0" height if low profile front trim is ordered.

- 74" max. Rack Height
- Door May Be Hinged Left or Right On Site
- Freight Class: 85

Physical Data	Model 40.5"D	Model 60.5"D	Model 80.5"D	Model 100.5" D	Model 120.5"D
Interior Dimensions	37.8"D x 32.6"W x 74.5"H	57.8"D x 32.6"W x 74.5" H	77.8"D x 32.6"W x 74.5"H	97.8"D x 32.6"W x 74.5"H	117.8"D x 32.6"W x 74.5"H
Exterior Dimensions	43.3"D x 42.0"W	63.3"D x 42.0"W	83.3"D x 42.0"W	103.3"D x 42.0"W	123.3"D x 42.0"W
Net Door Opening Height	74.5"	74.5"	74.5"	74.5"	74.5"
Net Door Opening Width	31.0"	31.0"	31.0"	31.0"	31.0"
Power Input with Neutral [Ⓐ]	208-240V/1/18-21A or 208-240V/3/18-21A	208-240V/1/18-21A or 208-240V/3/18-21A	208-240V/1/37-41A or 208-240V/3/32-36A	208-240V/1/37-41A or 208-240V/3/32-36A	208-240V/1/37-41A or 208-240V/3/32-36A
Heat Wattage (KW)	3.3-4.4	3.3-4.4	6.6-8.8	6.6-8.8	6.6-8.8
Water Flow Rate (GPM)	0.5	0.5	1.0	1.0	1.0
Max. Water Usage (GPH)	1.0	1.0	2.0	2.0	2.0

UTILITIES & NOTES

- Ⓛ **Water:** ½" FNPT cold water 30-80 psi at 85" (215.9 cm) AFF. Max. water usage varies by depth. See chart above for specific information.
- NOTE:** Water supply must have the proper hardness, pH & chloride concentration. Consult your local water company and/or water conditioner dealer before installation.
 - **Water hardness range:** 2-4 grains per gallon.
 - **pH range:** 7.0 to 8.0.
 - **Range for chloride concentration:** 0-30 ppm.
- Ⓜ **Drain:** ½" FNPT, front or rear drain at 5" (12.7 cm) AFF. Rte to air-gap drain.
- Ⓝ **Power:** Provide connection(s) at 85" (215.9 cm) AFF. See chart above for specific information.
 - Ⓐ Neutral wire circuitry needed to provide 110-120V for control components. A separate line may be run or a transformer will be required if 110-120V is not available.
- Installation:** Floor should be level within ⅛" per foot for proper installation. Slope should not exceed ¾" in all directions under the unit.
- Ⓟ **Shipping:** Contact factory for shipping information.
- Important:**
 - Do not route utilities (wiring, plumbing, etc.) in or under the non-combustible floor beneath the proofer.
 - A minimum of 1" airgap between proofer and oven recommended to ensure proper proofer operation.
 - 10' ceiling height is recommended for proper airflow and service access.

SHORT SPECIFICATION

The proofer shall be of stainless steel construction, manufactured in the United States by Baxter Mfg. The unit footprint shall be no wider than 42.0" and have two height options to meet the needs of the site and the project. Built using modular panel construction with cam lock attachment, the proofer shall incorporate foam insulation and gaskets to form a strong, energy efficient enclosure. Nonmetallic Interior bumpers shall protect the interior on all sides.

The proofer shall include eye level, digital controls in the door and a patented air flow system. No ramp is required for this unit. The controls will independently set temperature and humidity for precise proofing control. Four individual count-down timers for products with different time requirements shall be provided. The air flow system will include an internally mounted humidifier. No flush cleaning is required. The proofer door shall be field reversible.

The proofer will bear the following agency approvals: UL for safety and sanitation for the U.S. and Canada.

Manufacturer reserves the right to make changes in sizes and specifications.



19220 State Route 162 East
Orting, WA 98360
www.baxtermfg.com

Factory
(360) 893-5554

Customer Care
(800) 777-2828
or
(800) 333-7447

Customer Care Fax
(937) 332-2852